

**PowerShot  
SX70 HS**

# BRIDGE CAMERA WITH VERSATILE FEATURES AND THE LOOK OF A DSLR



- Looks and feel of an all-in-one DSLR with easy-to-use interface
- Versatile shots with 65x zoom and 10fps shooting
- Capture important memories in RAW and 4K video
- Reliable, fast autofocus even in low light
- Phone and computer support via Bluetooth or Wi-Fi

Mighty, 65x zoom all-in-one combining DSLR looks with versatile, cutting-edge features. Support for images in RAW, 4K video, Bluetooth and Wi-Fi as well as the convenience of Remote Live View



**20.3** MEGA  
PIXELS  
HIGH-SENSITIVITY  
CMOS

**10**  
Frames  
Per Sec

**DiGiC**  
8

**4K**  
UHD

Wi-Fi

Bluetooth®

## PRODUCT RANGE



**PowerShot SX70 HS**



**PowerShot G3 X**



**PowerShot SX540 HS**

**PowerShot SX70 HS**  
PowerShot G3 X  
PowerShot SX540 HS  
PowerShot SX60 HS

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# PowerShot SX70 HS

<b>IMAGE SENSOR</b>		<b>LCD MONITOR</b>	
Type	1/2.3 type back-illuminated CMOS	Monitor	7.5 cm (3.0") Vari-Angle LCD (TFT), approx. 922,000 dots
Effective Pixels	Approx. 20.3M <sup>[14]</sup>	Coverage	Approx. 100%
Total Pixels	Approx. 21.1M	Brightness	Adjustable to one of five levels
Colour Filter Type	Primary Colour		
<b>IMAGE PROCESSOR</b>		<b>FLASH</b>	
Type	DIGIC 8	Modes	Auto, Manual Flash On / Off, Slow Synchro
<b>LENS</b>		X-Sync Speed	Fastest speed 1/2000 s
Focal Length	3.8 – 247.0 mm (35 mm equivalent: 21 – 1365 mm)	Red-Eye Reduction	Yes
Zoom	Optical 65x ZoomPlus 130x Digital approx. 4.0x (with Digital Tele-Converter Approx. 1.6x or 2.0x <sup>[11]</sup> ) Combined approx. 260x	Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments.
Maximum f/number	f/3.4 – f/6.5	Flash Exposure Lock	Yes
	15 elements in 11 groups (3 UD lenses, 1 double-sided aspherical lens)	Manual Power Adjustment	3 levels with internal flash
Construction	Yes (lens shift-type). Approx. 5 stop <sup>[13]</sup> Intelligent IS with Dual Sensing IS plus 5-axis Advanced Dynamic IS	Second Curtain Synchronisation	Yes
Image Stabilisation		Built-in Flash Range	approx 48 cm – 6.5 m (W) / 1.8m - 4 m (T)
<b>FOCUSING</b>		<b>SHOOTING</b>	
Type	TTL	Modes	Smart Auto (29 scenes detected), Hybrid Auto, Creative Shot, Program AE, Shutter priority AE, Aperture priority AE, Manual, Sports, SCN
AF System/ Points	Face & Tracking (9 points), Tracking, 1-point, Spot	Drive modes	Single, High-speed continuous, low-speed continuous
AF Modes	One Shot, Servo, Continuous	Continuous Shooting	Max: One Shot AF approx 10fps, Servo AF approx 7.4fps
AF Assist Beam	Yes		
Manual Focus	Yes, plus MF Peaking	<b>RECORDING PIXELS / COMPRESSION</b>	
Closest Focusing Distance	0 cm (W) from front of lens in Macro	Image Size	4:3 - (L) 5184 x 3888, (M) 3648 x 2736, (S) 2432 x 1824 16:9 - (L) 5184 x 2912, (M) 3648 x 2048, (S) 2432 x 1368 3:2 - (L) 5184 x 3456, (M) 3648 x 2432, (S) 2432 x 1616 1:1 - (L) 3888 x 3888, (M) 2736 x 2736, (S) 1824 x 1824
<b>EXPOSURE CONTROL</b>		Compression	Resize option available in playback
Metering modes	Evaluative, Centre-weighted average, Spot (except movie)	Movies	Fine, Normal (4K) 3840 x 2160, 29.97/25 fps (Full HD) 1920 x 1080, 59.94/50/29.97/25 fps, (HD) 1280 x 720, 59.94/50 fps Up to 29 min 59 s <sup>[7]</sup>
AE Lock	Yes	Movie Length	
Exposure Compensation	+/- 3 EV in 1/3 stop increments.	FILE TYPES	
ISO sensitivity	100-3200 in 1/3 stop increments	Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system 2.0, Digital Print Order Format [DPOF] Version 1.1 compliant
<b>SHUTTER</b>		Movies	MP4 [Video: MPEG-4 AVC / H.264, Audio: MPEG-4 AAC-LC (stereo)]
Speed	15 - 1/2000 s		
<b>WHITE BALANCE</b>		DIRECT PRINT	
Settings	Auto, Daylight, Shade, Cloudy, Tungsten, Fluorescent, Flash, Custom.	Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
<b>VIEWFINDER</b>		PictBridge	Yes (via USB or Wireless LAN)
Viewfinder	0.39 type, approx 2.36m dots		
Viewfinder / Coverage	approx 100%		
Dioptr Correction	approx -3.0 - +1.0 m-1 (dpt)		

Canon

Live for the story\_

# TECHNICAL SPECIFICATIONS

# PowerShot SX70 HS

## OTHER FEATURES

### GPS

GPS via Mobile (via Canon Camera Connect app with compatible smart devices)

### Red-Eye Correction

Yes, during shooting and playback

### Histogram

Yes, during playback

### Playback zoom

Approx. 2x – 10x

### Self Timer

Approx. 2, 10 s or Custom

### Menu Languages

English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew

## INTERFACE

### Computer

Hi-Speed USB dedicated connector (Micro-B compatible)

### Other

HDMI Micro (Type-D) Connector

### Computer/Other

Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only) <sup>[11]</sup>

## MEMORY CARD

### Type

SD, SDHC, SDXC (UHS-1 Speed Class 3 compatible)

## SUPPORTED OPERATING SYSTEM

### PC & Macintosh

Windows 10 / 8.1 / 8 / 7 SP1 <sup>[18]</sup>  
Mac OS X 10.9 / 10.10 / 10.11

For Wi-Fi connection to a PC:  
Windows 10 / 8.1 / 8 / 7 SP1  
Mac OS X 10.9 / 10.10

For Image Transfer Utility:  
Windows 10 / 8.1 / 8 / 7 SP1  
Mac OS X 10.9 / 10.10 / 10.11

## SOFTWARE

### Other

Image Transfer Utility

Camera Connect app available on iOS and Android devices

## POWER SOURCE

### Batteries

Rechargeable Li-ion Battery LP-E12 (battery and charger supplied)

### Battery life

Approx. 325 shots

Eco Mode: Approx. 405 shots  
Playback Mode: Approx. 360 min

### A/C Power Supply

Charging available with Compact Power Adapter CA-PS700 <sup>[17]</sup>

## ACCESSORIES

### Power Supply & Battery Chargers

Compact Power Adapter CA-DC30E  
Battery Charger CB-2LHE  
Rechargeable Li-ion Battery NB-13L

### Other

Interface cable IFC-600PCU

## PHYSICAL SPECIFICATIONS

### Operating Environment

0 – 40 °C, 10 – 90% humidity

### Dimensions (W x H x D)

127.1 x 90.9 x 116.6 mm

### Weight

Approx. 610 g (including battery and memory card)

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.

Subject to change without notice.

<sup>[11]</sup> Depending on the image size selected.

<sup>[2]</sup> Not all functions of the flash are supported.

<sup>[3]</sup> Under conditions where the flash does not fire.

<sup>[4]</sup> Depending on memory card speed / capacity / compression setting.

<sup>[5]</sup> 0 – 35 °C when NB4-300 is used.

<sup>[6]</sup> Some settings limit availability.

<sup>[7]</sup> The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.

<sup>[8]</sup> The shock resistant testing methods are unique to this product and do not guarantee against damage or malfunction of the product.

<sup>[9]</sup> Complies with the NMEA (National Marine Electronics Association of the U.S.) 0183

<sup>[10]</sup> GPS use may be restricted in certain countries or regions. Use of GPS should comply with the laws and regulations of the country and area in which it is being operated including any restriction on the use of electronics.

<sup>[11]</sup> Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit [www.canon-europe.com/wirelesscompacts](http://www.canon-europe.com/wirelesscompacts)

<sup>[12]</sup> Sustained continuous shooting function requires compatible SDHC/SDXC UHS Speed Class 1 memory card, total number of frames captured varies depending on shooting subject.

<sup>[13]</sup> Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

<sup>[14]</sup> Image processing may cause a decrease in the number of pixels.

<sup>[15]</sup> ISO sensitivity denotes Recommended Exposure Index

<sup>[16]</sup> Auto ND Filter not available in Movie Mode.

<sup>[17]</sup> Charging via USB requires Interface Cable IFC-600PCU (Sold separately) or similar cable with USB Micro-B to USB type-A connectors. Charging time varies depending on the remaining battery power.

<sup>[18]</sup> Software applications compatible with Windows 10 in Windows 10 Desktop Mode only

<sup>[20]</sup> Sustained continuous shooting speed is tested based on Canon's testing standard. Function requires compatible SDHC/SDXC UHS-1 Speed Class 3 memory card, total number of frames captured varies depending on shooting subject, settings and brand of memory card

<sup>[21]</sup> Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth

<sup>[22]</sup> Bluetooth connection requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later) as well as latest version of Camera Connect app installed

<sup>[23]</sup> Not compatible with following PictBridge compatible SELPHY CP200/ CP220/ CP300/ CP330/ CP400/ CP500/ CP600/ ES1

Live for the story\_

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2018

## BRIDGE CAMERA WITH VERSATILE FEATURES AND THE LOOK OF A DSLR

*PowerShot*  
**SX70 HS**

Mighty, 65x zoom all-in-one combining DSLR looks with versatile, cutting-edge features. Support for images in RAW, 4K video, Bluetooth and Wi-Fi as well as the convenience of Remote Live View

Sales Start Date: November 2018



### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
PowerShot SX70 HS BK EU26	3071C002AA	4549292119169

### OPTIONAL ACCESSORIES:

Product Name	Mercury Code	EAN Code
<b>Power Supply</b>		
Battery Pack LP-E12	6760B002AA	4960999913247
Battery Charger LC-E12E	6782B001AA	8714574626291
<b>Remote Control</b>		
Remote Switch RS-60E3	2469A002AA	4960999581354
Wireless Remote-Control BR-E1	2140C001AA	4549292087864
<b>Cable</b>		
USB Cable IFC-600PCU	1015C001AA	4549292054378
<b>Strap</b>		
PowerShot Neck Strap NS-100	0039X579	8714574617268
<b>Hood</b>		
Lens Hood LH-DC90	9843B001AA	4549292017755
<b>Filter Adapter</b>		
Filter Adapter FA-DC67A	4728B001AA	4960999677187

**Canon**

Live for the story\_

## BRIDGE CAMERA WITH VERSATILE FEATURES AND THE LOOK OF A DSLR

# PowerShot SX70 HS

Mighty, 65x zoom all-in-one combining DSLR looks with versatile, cutting-edge features. Support for images in RAW, 4K video, Bluetooth and Wi-Fi as well as the convenience of Remote Live View



### MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
PowerShot SX70 HS BK EU26	3071C002AA	EA	Each	1	18.95	13.9	13.35	1.093
		CT	Carton	6	42.5	30	22.6	7.17
		EP	Euro Pallet	144	120	80	105.4	182
			Layers per Pallet	4				
			Cartons per Layer	6				
			Products per layer	36				

### What's in the box?

- Compact Power Adapter CA-DC30E
- Battery Charger CB-2LHE
- Rechargeable Li-ion Battery NB-13L
- Interface cable IFC-600PCU

# Canon

Live for the story\_