

# Speedlite Transmitter ST-E3-RT(Ver.2)

## REMOTE FLASH TRIGGER FOR SPEEDLITE FLASHES

Fire compatible Speedlite flashguns over distances of up to 30m. Radio-frequency control provides reliable operation even when direct line of sight is not possible. Additional features for the Speedlite EL-1.



- Reliable off-camera flash control
- Multiple flash photography
- Remote camera control
- Easy to use design
- Wireless second curtain sync\*

### PRODUCT RANGE



Speedlite Transmitter ST-E3-RT(Ver.2)



Speedlite Transmitter ST-E3-RT



Speedlite Transmitter ST-E2

Speedlite Transmitter ST-E3-RT(Ver.2)

Speedlite Transmitter ST-E3-RT

Speedlite Transmitter ST-E2

**Canon**

Live for the story\_

\*See specifications for full details

# TECHNICAL SPECIFICATIONS

## Speedlite Transmitter ST-E3-RT(Ver.2)

### FLASH MODES

Auto exposure control	E-TTL II / E-TTL
High speed sync (FP)	Yes
Manual / output settings	Yes - 1/1- 1/128 (1/8192 <sup>1,2</sup> )
Manual steps	1/3 step
Strobe / output settings	Yes - 1/4-1/128 (1/8192 <sup>1,2</sup> )
Frequency	1-500Hz

### FLASH-RELATED FUNCTION

FE lock	Yes
FE Memory	Yes <sup>1,4</sup>
Flash exposure compensation	Yes
Flash Exposure bracketing	Yes
Second-curtain flash sync	Yes <sup>1,3</sup>
Modelling flash	Yes

### WIRELESS FLASH

Transmitter	Yes
Transmission type	Radio
Transmitter Max range approx.	Indoors: 30m Outdoors: 30m
Receiver	No
No of groups	5 - A,B,C,D or E
No of channels	15
Remote Shutter Release	Yes

### AF ASSIST

AF-assist beam	No
Number of AF points supported	-
AF-assist beam type	-

### POWER SOURCE

Battery	2 x AA batteries
Minimum recycling time	N/A
External power supply	No

### CONSTRUCTION

Dust and water resistance	Yes
Mounting foot material	Metal

### Misc.

Custom function	8 (4 personal functions)
Flash settings from camera menus	Yes
External flash exposure sensor	No
PC terminal	No
Accessories	<b>Included:</b> Soft case <b>Optional:</b> Off-Camera Shoe Cord OC-E3, Release Cable SR-N3
Compatible Speedlites	EL-1, 600EX II-RT, 600EX-RT, 430EX III-RT
Dimensions & weight	
Size (W x H x D), mm	67.4 x 61.5 x 77.4
Weight (Excluding batteries), grams	110g

### Footnotes

- <sup>1</sup> Compatible cameras may need the latest firmware update.
- <sup>2</sup> Minimum flash output of 1/8192 possible with Speedlite EL-1 only (1/128 with high-speed sync). Does not show in the camera's UI settings on cameras launched before 2020.
- <sup>3</sup> With compatible cameras launched from 2020, e.g. EOS-1D X Mark III, EOS R5/R6 and later, but excluding EOS 850D.
- <sup>4</sup> Flash output amount may slightly differ between that of E-TTL autofocus and manual flash



Live for the story\_

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2021

# REMOTE FLASH TRIGGER FOR SPEEDLITE FLASHES

## Speedlite Transmitter ST-E3-RT(Ver.2)

Fire compatible Speedlite flashguns over distances of up to 30m. Radio-frequency control provides reliable operation even when direct line of sight is not possible. Additional features for the Speedlite EL-1.



Sales Start Date: Late May 2021

### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
Speedlite Transmitter ST-E3-RT(Ver.2)	5743B012AA	4549292192568

### MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
Speedlite Transmitter ST-E3-RT(Ver.2)	5743B012AA	EA	Each	1	16	11.8	11.2	0.65
		CT	Carton	24	47	37.5	36.9	17.2
		EP	Euro Pallet	192	120	80	88.8	148
			Layers per Pallet	2				
			Cartons per Layer	4				
			Products per layer	96				

### What's in the box?

- Speedlite Transmitter ST-E3-RT(Ver.2)
- Soft Case

Live for the story\_