



## Compact Flash RICOH GF-2:

External Flash RICOH GF-2.

With a maximum guide number of 3 (at ISO 100/m), this super-compact, ultra-lightweight accessory flash unit provides an auto flash function when mounted on the RICOH GR IV compact digital camera body.



## Features of RICOH GF-2

### Super-compact design

Exclusively designed for use with the RICOH GR IV high-end digital compact camera, the GF-2 features a super-compact body for outstanding portability, making it perfect for carrying in a pocket without the need to remove it from the camera body.

### Simple, effortless operations

When mounted on the RICOH GR IV and the camera set to the ISO Auto Flash mode, the GF-2 allows the camera to automatically adjust its guide-number and ISO sensitivity settings according to the subject's distance. This flash mode enhances the GR IV's snapshot operations in casual flash photography.\*

\* When mounted on a RICOH GR-series model other than the GR IV, the GF-2 only operates in the full-discharge mode, because the alignment of flash contacts (except for the X-sync contact) differs from that of the GR IV.

The firmware designed to allow a GR-III-series camera to automatically adjust the discharge level according to its focusing status is currently under development. This firmware is scheduled to be released in October 2025.

### Built-in lithium-ion battery

The GF-2 incorporates a rechargeable lithium-ion battery, which can be charged via an USB Type-C terminal. Even when the camera's battery runs low, this built-in battery stabilizes the flash discharge level.

Packing Information	
Dimensions	96 x 76 x 36 mm
Weight	67 g
Article Codes	
	Art No. 35306 / UPC Code 0027075311596 - RICOH GF-2
Market Launch	
	September 2025

## RICOH GF-2 Specifications

Type	Clip-on type external flash
Guide number	3 (ISO 100), 6 (ISO 400)
Flash mode*1	Guide number control by interlocking with camera rangefinder, manual flash (1/1, 1/4)
Flash angle	18mm focal length (wide conversion lens is not supported*2) Up and down angle: 47° Left and right angle: 66°
Flash interval	Approx. 2 seconds
Number of flashes	Approx. 270 times (when fully charged)
Power supply	Rechargeable lithium-ion battery (not replaceable)
Charging method	USB Type-C (5 V, 0.1 A or more)
Charging time	Approx. 2 hours
Operating temperature	0 to 40°C (32 to 104°F)
Operating humidity	85% or less (no condensation)
Storage temperature	-20 to 45°C (-4 to 113°F) (for 3 months)
Dimensions and weight	Approx. 51 (W) × 17 (H) × 31 (D) mm (Approx. 2.0 (W) × 0.7 (H) × 1.2 (D) in.) Approx. 19 g (Approx. 0.7 oz)

\*1 When installed on GR IV

\*2 Vignetting occurs due to the lens frame of GW-4